

W.Nr.1.2311

thickness	32		27		36		46		56		66		76		86		96		106		116		126		
w x l	stock pcs	EUR/pc	stock pcs	EUR/pc	stock pcs	EUR/pc	stock pcs	EUR/pc	stock pcs	EUR/pc	stock pcs	EUR/pc	stock pcs	EUR/pc	stock pcs	EUR/pc	stock pcs	EUR/pc	stock pcs	EUR/pc	stock pcs	EUR/pc	stock pcs	EUR/pc	
156 x 156									1	23															
156 x 196					2	19	5	24	3	28	5	32	3	37											
156 x 246											2	41													
156 x 296																									
156 x 346							1	40																	
196 x 196	1	16	8	19	7	24	4	29					4	46											
196 x 246					2	30	2	36	3	43	4	50			1	64									
196 x 296					1	36	2	44	2	52	2	60			1	68									
196 x 346																									
196 x 396							2	59					1	91											
246 x 246					3	44	8	55			5	62	2	72											
246 x 296					2	52	2	64	1	76	4	88	1	100											
246 x 346					2	59	1	73							1	127									
296 x 296					4	53	6	65			6	90	7	102	3	115	3	127							
296 x 346			1	49	1	62	11	76	4	90	3	104	5	119	5	133	1	148	2	161					
296 x 396							3	86			2	120	2	137	1	152	1	169	1	184	2	202			
346 x 446					2	79	2	97			1	134													
346 x 346					1	72	1	89							1	156									
346 x 396					2	101	1	120	3	139					2	178									
396 x 396					1	94	1	115	2	138															
496 x 496									1	212				1	280	3	314							1	451

\* plates are milled in tol. +1,0/+2,0 mm,  
 \* after cutting are plates stress-relief annealed,